




Vap	TB874 SERIES
Bright	TC874 SERIES
TiN	TD874 SERIES

UNF Unified fine threads

● Unified Feingewindea
● UNF
● Unificato passo grosso

► For using multi-purpose and correct thread profiles & long tool life due to special tap geometry. YG-1 company has a patent.

► Für vielfältigen Einsatz, genaue Gewindeprofile und lange Standzeitendank einer besonderen Schneidengeometrie. Von YG-1 patentiert.



Material groups: **MU** HSS-E DIN 371/374 2B 60° B Vap Bright TiN

Machine taps
Maschinengewindebohrer

Recommended Cutting Page : P.116

Unit : mm

SIZE	TPI	EDP No.			Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
		Vap	Bright	TiN								
ØD1		L1	L2	L3	ØD2	K	KI	Z	Ød1			
#4 - 48 UNF	TB874182	TC874182	TD874182	11	56	18	3.5	2.7	6	3	2.4	
#5 - 44 UNF	TB874222	TC874222	TD874222	11	56	18	3.5	2.7	6	3	2.7	
#6 - 40 UNF	TB874262	TC874262	TD874262	12	56	20	4	3	6	3	3	
#8 - 36 UNF	TB874302	TC874302	TD874302	13	63	21	4.5	3.4	6	3	3.5	
#10 - 32 UNF	TB874342	TC874342	TD874342	15	70	25	6	4.9	8	3	4.1	
#12 - 28 UNF	TB874382	TC874382	TD874382	16	80	30	6	4.9	8	3	4.7	
1/4 - 28 UNF	TB874422	TC874422	TD874422	17	80	30	7	5.5	8	3	5.5	
5/16 - 24 UNF	TB874462	TC874462	TD874462	17	90	35	8	6.2	9	3	6.9	
3/8 - 24 UNF	TB874502	TC874502	TD874502	18	100	39	9	7	10	3	8.5	
7/16 - 20 UNF	TB874542	TC874542	TD874542	22	100	40	8	6.2	9	3	9.9	
1/2 - 20 UNF	TB874582	TC874582	TD874582	22	100	40	9	7	10	3	11.5	
9/16 - 18 UNF	TB874622	TC874622	TD874622	22	100	40	11	9	12	3	12.9	
5/8 - 18 UNF	TB874662	TC874662	TD874662	22	100	40	12	9	12	3	14.5	
3/4 - 16 UNF	TB874722	TC874722	TD874722	25	110	44	14	11	14	4	17.5	
7/8 - 14 UNF	TB874762	TC874762	TD874762	26	125	50	18	14.5	17	4	20.5	
1 - 12 UNF	TB874802	TC874802	TD874802	28	140	54	20	16	19	4	23.25	

►DIN 371(#4~3/8) and DIN 374(7/16~1)
 * The other coating(TiCN or TiAlN) is available on your request.

◎ : Excellent ○ : Good

ISO	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
Material Description	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VDI 3323																				
HRc																				
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	◎	◎	◎	◎	○	○	◎	◎	◎	◎	◎	◎	◎		

ISO	N									S							H				
	Aluminum-wrought alloy			Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron
Material Description	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
VDI 3323																					
HRc																					
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended			◎			◎	◎	◎													



RECOMMENDED CUTTING CONDITIONS
EMPFOHLENE SCHNEIDKONDITIONEN

THREAD MILLS					TB744	TC814	TD814	TB814	TCJ05	TDJ05	TBJ05	TCJ06		
	SYNCHRO TAPS					TB754	TC854	TD854	TB854	TCJ09			TDJ09	
COMBO TAPS					TQ744	TC834	TD834	TB834	TCJ01	TDJ01				
YG TAP GENERAL					TQ754	TC874	TD874	TB874	TCJ02	TDJ02				
YG TAP STEEL	ISO	VDI 3323	Material Description	HB	HRc	Vc (m/min)								
YG TAP HARDENED	P	1	Non-alloy steel	125			15-20	20-25	15-20	15-20	20-25	15-20	15-20	
		2		190	13	15-20	15-20	20-25	15-20	15-20	20-25	15-20	15-20	
		3		250	25		12-18	18-24	12-18	12-18	18-24	12-18	12-18	
		4		270	28	10-15	10-15	15-20	10-15	10-15	15-20	10-15	10-15	
		5		300	32		6-10	10-14	6-10	6-10	10-14	6-10	6-10	
		6	Low alloy steel	180	10	10-15	10-15	15-20	10-15	10-15	15-20	10-15	10-15	
		7		275	29	10-15	10-15	15-20	10-15	10-15	15-20	10-15	10-15	
		8		300	32		6-10	10-14	6-10	6-10	10-14	6-10	6-10	
		9		350	38		3-5	5-7	3-5	3-5	5-7	3-5	3-5	
		10		High alloyed steel, and tool steel	200	15		3-5	5-7	3-5	3-5	5-7	3-5	3-5
		11			325	35								
YG TAP CAST IRON	M	12	Stainless steel	200	15	7-10	7-10	10-15	7-10	7-10	10-15	7-10	7-10	
		13		240	23	5-8	5-8	8-11	5-8	5-8	8-11	5-8	5-8	
		14		180	10	4-6	4-6	6-8	4-6	4-6	6-8	4-6	4-6	
YG TAP ALU	K	15	Grey cast iron	180	10		10-15	15-20	10-15	10-15	15-20	10-15	10-15	
		16		260	26		5-8	8-11	5-8	5-8	8-11	5-8	5-8	
		17	Nodular cast iron	160	3		10-15	15-20	10-15	10-15	15-20	10-15	10-15	
		18		250	25		5-8	8-11	5-8	5-8	8-11	5-8	5-8	
		19		130										
20	Malleable cast iron	230	21											
NUT TAPS	N	21	Aluminum-wrought alloy	60										
		22		100										
		23	Aluminum-cast, alloyed	75			15-20	20-25	15-20	15-20	20-25	15-20	15-20	
		24		90										
		25		130										
		26		110			25-35	35-40	25-35	25-35	35-40	25-35	25-35	
		27	Copper and Copper Alloys (Bronze / Brass)	90			8-12	12-17	8-12	8-12	12-17	8-12	8-12	
		28		100		15-20	15-20	20-25	15-20	15-20	20-25	15-20	15-20	
		29		Non Metallic Materials										
		30												
PIPE TAPS	S	31	Heat Resistant Super Alloys	200	15									
		32		280	30									
		33		250	25									
		34		350	38									
		35		320	34									
		36	Titanium Alloys	400 Rm										
		37		1050 Rm										
TECHNICAL DATA	H	38	Hardened steel	550	55									
		39		630	60									
		40	Chilled Cast Iron	400	42									
		41	Hardened Cast Iron	550	55									

SURFACE TREATMENT AND COATING

The applied High Speed Steels holds a grant of good wear resistance and toughness. Therefore YG-1 normally delivers taps with bright and unfinished surface. For certain materials, various surface treatments provide higher advantage in machining.

STEAM TEMPERED - Vap

Steam Tempered is a Fe₃O₄-oxyd-coating which reduces friction between the tool and workpiece, also preventing cold welding.

NITRIDING - NI

Recommend surface treatment for machining materials that affect wear abrasion, such as grey cast iron, alu-alloys with high Si-percentages (more than 10%).

Below are the various surface treatments for excellent finish surfaces suitable for many applications. The surface treatments are produced and developed within the company.

TiN-COATING

TiN-coating yields a hardness of approx. 2,300 HV and also a heat resistant up to approx. 600°C. The current coating is an excellent all-round coating for normal applications.

Colour : Golden Coefficient of friction against steel : 0.4

TiCN-COATING

TiCN takes place of TiN when the conditions require the coating to have a different hardness and toughness.

The TiCN brings advantages for machining very difficult steels or cutting interrupted bores.

The TiCN-coating has a hardness of approx. 3,000 HV, but is heat resistance only holds up to approx. 400°C, meaning that the TiCN needs an excellent cooling system for a long service life.

Colour : Blue-Grey Coefficient of friction against steel : 0.4

TiAlN-COATING

A special coating for machining abrasive materials such as grey cast iron, alu-alloys with silicon, fiber reinforced plastics, etc., or machining at high temperatures with insufficient cooling, or at high speeds ≥ 600 m/min. TiAlN has a hardness of approx. 3,000 HV and is heat resistant up to approx. 800°C.

Colour : Violet-Grey Coefficient of friction against steel : 0.4

Hardslick-COATING

Hardslick combines the advantages of an extremely hard, thermally stable TiAlN-coating with the sliding and lubricating properties of an outer WC/C(Tungsten carbide/carbon)-coating in a novel way. The Hardslick coating has a hardness of approx. 3,000 HV and is temperature-resistant up to approx. 800°C.

Colour : Violet-Grey Coefficient of friction against steel : 0.2

SELECTION GUIDE



HSS-E & HSS-PM COMBO TAPS

For Multi Purpose Tapping
YG-1's Patent



Please visit globalyg1.com/mat for material search

◎ : Excellent ○ : Good

Recommended cutting conditions : P.114

HOLE TYPE		Max. 3.0xD Through Hole						
TOOL MATERIAL		HSS-E						
CHAMFER LEAD ACC. TO DIN2197		B	B	B	B	B	B	
FLUTE TYPE		Spiral Point	Spiral Point	Spiral Point	Spiral Point	Spiral Point	Spiral Point	
SPIRAL FLUTE ANGLE		-	-	-	-	-	-	
SERIES	M	DIN 371/376	TC814 (P95)	TD814 (P95)	TB814 (P95)	TCJ05 (P96)	TDJ05 (P96)	TBJ05 (P96)
		DIN352						
		DIN357/LONG						
	MF	DIN374	TC854 (P100)	TD854 (P100)	TB854 (P100)	TCJ09 (P102)	TDJ09 (P102)	
		DIN2181						
	UNC	DIN 371/376	TC834 (P109)	TD834 (P109)	TB834 (P109)	TCJ01 (P110)	TDJ01 (P110)	
		DIN351						
	UNF	DIN 371/374	TC874 (P111)	TD874 (P111)	TB874 (P111)	TCJ02 (P112)	TDJ02 (P112)	
		DIN2181						
	BSW	DIN2182/2183						
		DIN351						
	G(BSP)	DIN5156/5157						
	EG-M	DIN 371/376						
	EG-UNC	DIN 371/376						
EG-UNF	DIN 371/374							
SURFACE TREATMENT		Bright	TiN	VAP	Bright	TiN	VAP	
MODEL								

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment	HB	HRC	Bright	TiN	VAP	Bright	TiN	VAP	
P	1	Non-alloy steel	About 0.15% C Annealed	125		○	○	○	○	○	○	
	2		About 0.45% C Annealed	190	13	◎	◎	◎	◎	◎	◎	
	3		About 0.45% C Quenched & Tempered	250	25	◎	◎	◎	◎	◎	◎	
	YG TAP Ti Ni	4	Low alloy steel	About 0.75% C Annealed	270	28	◎	◎	◎	◎	◎	◎
		5		About 0.75% C Quenched & Tempered	300	32	◎	◎	◎	◎	◎	◎
		6		Annealed	180	10	◎	◎	◎	◎	◎	◎
		7		Quenched & Tempered	275	29	◎	◎	◎	◎	◎	◎
	YG TAP FORMING	8	High alloyed steel, and tool steel	Quenched & Tempered	300	32	◎	◎	◎	◎	◎	◎
		9		Quenched & Tempered	350	38	◎	◎	◎	◎	◎	◎
		10		Annealed	200	15	○	○	○	○	○	○
		11		Quenched & Tempered	325	35						
M	12	Stainless steel	Ferritic / Martensitic Annealed	200	15	◎	◎	◎	◎	◎	◎	
	13		Martensitic Quenched & Tempered	240	23	◎	◎	◎	◎	◎	◎	
	14		Austenitic	180	10	◎	◎	◎	◎	◎	◎	
K	15	Grey cast iron	Pearlitic / ferritic	180	10	◎	◎	◎	◎	◎	◎	
	16		Pearlitic (Martensitic)	260	26	◎	◎	◎	◎	◎	◎	
	PIPE TAPS	17	Nodular cast iron	Ferritic	160	3	◎	◎	◎	◎	◎	◎
		18		Pearlitic	250	25	◎	◎	◎	◎	◎	◎
		19		Ferritic	130							
20	Malleable cast iron	Pearlitic	230	21								
N	21	Aluminum-wrought alloy	Not Curable	60								
	22		Curable Hardened	100								
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable	75		◎	◎	◎	◎	◎	◎	
	24		≤ 12% Si, Curable Hardened	90								
	25		> 12% Si, Not Curable	130								
	26	Copper and Copper Alloys (Bronze / Brass)	Cutting Alloys, PB>1%	110		◎	◎	◎	◎	◎	◎	
	27		CuZn, CuSnZn (Brass)	90		◎	◎	◎	◎	◎	◎	
	28		CuSn, lead-free copper and electrolytic copper	100		◎	◎	◎	◎	◎	◎	
	29	Non Metallic Materials	Duroplastic, Fiber Reinforced Plastic									
	30		Rubber, Wood, etc.									
S	31	Heat Resistant Super Alloys	Fe Based Annealed	200	15							
	32		Cured	280	30							
	33		Annealed	250	25							
	34		Ni or Co Based Cured	350	38							
	35		Cast	320	34							
	36	Titanium Alloys	Pure Titanium	400 Rm								
	37		Alpha + Beta Alloys Hardened	1050 Rm								
H	38	Hardened steel	Hardened	550	55							
	39		Hardened	630	60							
	40	Chilled Cast Iron	Cast	400	42							
	41	Hardened Cast Iron	Hardened	550	55							