


3 FLUTE SHORT END MILLS



P.17~20

Unit : mm

EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Overall Length
Non Coating	TiAIN	e8	h6		
ESH573020	EHC573020	2.0	6	7	51
ESH573030	EHC573030	3.0	6	8	52
ESH573040	EHC573040	4.0	6	11	55
ESH573050	EHC573050	5.0	6	13	57
ESH573060	EHC573060	6.0	6	13	57
ESH573070	EHC573070	7.0	10	16	66
ESH573080	EHC573080	8.0	10	19	69
ESH573090	EHC573090	9.0	10	19	69
ESH573100	EHC573100	10.0	10	22	72
ESH573110	EHC573110	11.0	12	22	79
ESH573120	EHC573120	12.0	12	26	83
ESH573130	EHC573130	13.0	12	26	83
ESH573140	EHC573140	14.0	12	26	83
ESH573150	EHC573150	15.0	12	26	83
ESH573160	EHC573160	16.0	16	32	92
ESH573170	EHC573170	17.0	16	32	92
ESH573180	EHC573180	18.0	16	32	92
ESH573190	EHC573190	19.0	16	32	92
ESH573200	EHC573200	20.0	20	38	104
ESH573210	EHC573210	21.0	20	38	104
ESH573220	EHC573220	22.0	20	38	104
ESH573230	EHC573230	23.0	20	38	104
ESH573240	EHC573240	24.0	25	45	121
ESH573250	EHC573250	25.0	25	45	121
ESH573280	EHC573280	28.0	25	45	121
ESH573300	EHC573300	30.0	25	45	121
ESH573320	EHC573320	32.0	32	53	133

Tolerances according to DIN 7160 & 7161

Tolerance range in μm						
Nominal-Diameter in μm						
	from 1 to 3	over 3 to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50
e8	-14 -28	-20 -38	-25 -47	-32 -59	-40 -73	-50 -89
h6	0 -6	0 -8	0 -9	0 -11	0 -13	0 -16


3 FLUTE TiAIN COATED - SLOTTING

EHC573, EHC516 Series

MATERIAL	CARBON STEELS ALLOY STEELS TOOL STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS			
HARDNESS					~ HRc20				HRc20 ~ HRc30			
STRENGTH	~ 500N/mm ²				500 ~ 800N/mm ²				800 ~ 1000N/mm ²			
DIAMETER	RPM	FEED	V _c	f _z	RPM	FEED	V _c	f _z	RPM	FEED	V _c	f _z
2.0	7900	50	50	0.002	6300	35	40	0.002	5600	30	35	0.002
3.0	4900	70	45	0.005	4500	50	40	0.004	3500	35	35	0.003
4.0	3900	85	50	0.007	3100	60	40	0.006	2500	40	30	0.005
5.0	3100	110	50	0.012	2500	75	40	0.010	2200	55	35	0.008
6.0	2500	110	45	0.015	2200	90	40	0.014	1700	55	30	0.011
8.0	2000	125	50	0.021	1500	100	40	0.022	1300	70	35	0.018
10.0	1500	125	45	0.028	1300	110	40	0.028	1100	75	35	0.023
12.0	1300	140	50	0.036	1100	110	40	0.033	880	75	35	0.028
14.0	1100	140	50	0.042	980	100	45	0.034	780	75	35	0.032
16.0	980	140	50	0.048	780	100	40	0.043	630	70	30	0.037
18.0	880	125	50	0.047	700	100	40	0.048	560	70	30	0.042
20.0	780	125	50	0.053	630	100	40	0.053	560	70	35	0.042
22.0	700	125	50	0.060	630	100	45	0.053	490	70	35	0.048
25.0	630	110	50	0.058	560	90	45	0.054	430	55	35	0.043
28.0	560	100	50	0.060	490	75	45	0.051	390	50	35	0.043
30.0	490	85	45	0.058	430	70	40	0.054	350	40	35	0.038
32.0	490	85	50	0.058	390	65	40	0.056	310	40	30	0.043

MATERIAL	CARBON STEELS ALLOY STEELS TOOL STEELS				ALUMINUM ALUMINUM ALLOYS			
HARDNESS	HRc30 ~ HRc40							
STRENGTH	1000 ~ 1300N/mm ²							
DIAMETER	RPM	FEED	V _c	f _z	RPM	FEED	V _c	f _z
2.0	3100	15	20	0.002	16800	150	105	0.003
3.0	2200	20	20	0.003	15400	240	145	0.005
4.0	1500	30	20	0.007	11200	280	140	0.008
5.0	1300	30	20	0.008	8800	290	140	0.011
6.0	1100	35	20	0.011	7800	290	145	0.012
8.0	780	40	20	0.017	5600	360	140	0.021
10.0	630	40	20	0.021	4300	380	135	0.029
12.0	560	50	20	0.030	3500	360	130	0.034
14.0	490	50	20	0.034	3100	340	135	0.037
16.0	390	40	20	0.034	2800	340	140	0.040
18.0	350	40	20	0.038	2500	340	140	0.045
20.0	310	40	20	0.043	2200	310	140	0.047
22.0	310	40	20	0.043	1950	280	135	0.048
25.0	250	30	20	0.040	1700	270	135	0.053
28.0	220	30	20	0.045	1500	250	130	0.056
30.0	220	30	20	0.045	1500	250	140	0.056
32.0	200	30	20	0.050	1400	225	140	0.054

RPM = rev./min.
Feed = mm/min.
V_c = m/min.
f_z = mm/tooth



*The FEED, in long & extra long types, should be reduced by around 50%


3 FLUTE TiAIN COATED - SIDE CUTTING

EHC573, EHC516 Series

MATERIAL	CARBON STEELS ALLOY STEELS TOOL STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS			
HARDNESS					~ HRc20				HRc20 ~ HRc30			
STRENGTH	~ 500N/mm ²				500 ~ 800N/mm ²				800 ~ 1000N/mm ²			
DIAMETER	RPM	FEED	V _c	f _z	RPM	FEED	V _c	f _z	RPM	FEED	V _c	f _z
2.0	7900	85	50	0.004	6300	55	40	0.003	5600	50	35	0.003
3.0	4900	110	45	0.007	4500	85	40	0.006	3500	60	35	0.006
4.0	3900	145	50	0.012	3100	105	40	0.011	2500	70	30	0.009
5.0	3100	190	50	0.020	2500	130	40	0.017	2200	90	35	0.014
6.0	2500	190	45	0.025	2200	155	40	0.023	1700	90	30	0.018
8.0	2000	210	50	0.035	1500	170	40	0.038	1300	110	35	0.028
10.0	1500	210	45	0.047	1300	170	40	0.044	1100	125	35	0.038
12.0	1300	230	50	0.059	1100	190	40	0.058	880	125	35	0.047
14.0	1100	230	50	0.070	980	170	45	0.058	780	125	35	0.053
16.0	980	230	50	0.078	780	170	40	0.073	630	110	30	0.058
18.0	880	210	50	0.080	700	170	40	0.081	560	110	30	0.065
20.0	780	210	50	0.090	630	170	40	0.090	560	110	35	0.065
22.0	700	210	50	0.100	630	170	45	0.090	490	110	35	0.075
25.0	630	190	50	0.101	560	155	45	0.092	430	90	35	0.070
28.0	560	170	50	0.101	490	130	45	0.088	390	85	35	0.073
30.0	490	145	45	0.099	430	110	40	0.085	350	75	35	0.071
32.0	490	145	50	0.099	390	105	40	0.090	310	70	30	0.075

MATERIAL	CARBON STEELS ALLOY STEELS TOOL STEELS				ALUMINUM ALUMINUM ALLOYS			
HARDNESS	HRc30 ~ HRc40							
STRENGTH	1000 ~ 1300N/mm ²							
DIAMETER	RPM	FEED	V _c	f _z	RPM	FEED	V _c	f _z
2.0	3100	20	20	0.002	16800	250	105	0.005
3.0	2200	30	20	0.005	15400	390	145	0.008
4.0	1500	40	20	0.009	11200	460	140	0.014
5.0	1300	50	20	0.013	8800	490	140	0.019
6.0	1100	60	20	0.018	7800	490	145	0.021
8.0	780	70	20	0.030	5600	620	140	0.037
10.0	630	70	20	0.037	4300	630	135	0.049
12.0	560	75	20	0.045	3500	600	130	0.057
14.0	490	75	20	0.051	3100	560	135	0.060
16.0	390	70	20	0.060	2800	560	140	0.067
18.0	350	70	20	0.067	2500	560	140	0.075
20.0	310	70	20	0.075	2200	500	140	0.076
22.0	310	70	20	0.075	1950	480	135	0.082
25.0	250	50	20	0.067	1700	450	135	0.088
28.0	220	40	20	0.061	1500	420	130	0.093
30.0	220	40	20	0.061	1500	420	140	0.093
32.0	200	40	20	0.067	1400	380	140	0.090

RPM = rev./min.
Feed = mm/min.
V_c = m/min.
f_z = mm/tooth



*The FEED, in long & extra long types, should be reduced by around 50%