



# MORSE TAPER SHANK DRILLS

**D1206** SERIES

## HSS, MORSE TAPER SHANK TWIST DRILLS


**LONG**

- HSS, SPIRALBOHRER mit MORSEKEGELSCHAFT
- Forets HSS, queue cône morse, série longue
- PUNTE ELICOIDALI IN HSS, ATTACCO CM

**LANG**  
**LONGUE**  
**LUNGA**

- **Surface treatment** : Steam Tempered(Black Oxide Finish)
- **Application** : Drilling deep holes in steels, cast steels alloyed and non-alloyed, grey cast iron, malleable cast iron, graphite.

- **Oberflächenbehandlung** : Steam Homo(Schwarzoxidation)
- **Verwendung** : Für Bohrungen mit Bohrbuchsen oder an tief liegenden Stellen.  
Zum Bohren von Stahl und Stahlguß, Grauß, Temperguß, Sphäroguß, Sinterisen, Neusilber und Graphit.



Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length	Morse Taper No.
	D1	L1	L2	
D1206130	13.0	134	215	1
D1206135	13.5	142	223	1
D1206140	14.0	142	223	1
D1206145	14.5	147	245	2
D1206150	15.0	147	245	2
D1206155	15.5	153	251	2
D1206160	16.0	153	251	2
D1206165	16.5	159	257	2
D1206170	17.0	159	257	2
D1206175	17.5	165	263	2
D1206180	18.0	165	263	2
D1206185	18.5	171	269	2
D1206190	19.0	171	269	2

EDP No.	Drill Diameter	Flute Length	Overall Length	Morse Taper No.
	D1	L1	L2	
D1206195	19.5	177	275	2
D1206200	20.0	177	275	2
D1206210	21.0	184	282	2
D1206220	22.0	191	289	2
D1206230	23.0	198	296	2
D1206240	24.0	206	327	3
D1206250	25.0	206	327	3
D1206260	26.0	214	335	3
D1206270	27.0	222	343	3
D1206280	28.0	222	343	3
D1206290	29.0	230	351	3
D1206300	30.0	230	351	3

TAPER SHANK DRILLS

ISO	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	◎	◎	○	◎	◎	○	○	◎	◎	◎	○	○	◎	○	○	○	○	○	○

ISO	N					S										H					
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
HB											15	30	25	38	34			55	60	42	55
Recommended	○	○	○						○							○					

# MORSE TAPER SHANK DRILLS

## RECOMMENDED CUTTING CONDITIONS EMPFOLHENE SCHNEIDKONDITIONEN

### DL205, D1205, D1206, D1209, D1210 SERIES

### HSS&HSS-E, MORSE TAPER SHANK DRILLS

RPM = rev./min.  
FEED = mm/rev.

ISO	VDI 3323	Material Description	Vc (m/min)	Parameter	Drill Diameter (mm)																															
					13.0	16.0	18.0	20.0	30.0	40.0	50.0	60.0																								
P	1	Non-alloy steel	30	RPM	730	600	530	480	320	240	190	160																								
				FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																								
			2	25	RPM	610	500	440	400	270	200	160	130																							
					FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																							
			3	20	RPM	490	400	350	320	210	160	130	110																							
	FEED	0.11~0.17			0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																									
	4	15	RPM	370	300	270	240	160	120	100	80																									
			FEED	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18	0.14~0.20	0.16~0.22	0.18~0.24																									
	6	Low alloy steel	25	RPM	610	500	440	400	270	200	160	130																								
				FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																								
			20	RPM	490	400	350	320	210	160	130	110																								
FEED				0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																									
15			RPM	370	300	270	240	160	120	100	80																									
	FEED	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18	0.14~0.20	0.16~0.22	0.18~0.24																											
10	High alloyed steel, and tool steel	15	RPM	370	300	270	240	160	120	100	80																									
			FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																									
M	12	Stainless steel	20	RPM	490	400	350	320	210	160	130	110																								
				FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																								
			15	RPM	370	300	270	240	160	120	100	80																								
FEED	0.11~0.17	0.12~0.18		0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																											
K	15	Grey cast iron	30	RPM	730	600	530	480	320	240	190	160																								
				FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																								
	16	25	RPM	610	500	440	400	270	200	160	130																									
			FEED	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18	0.14~0.20	0.16~0.22	0.18~0.24																									
	17	Nodular cast iron	30	RPM	730	600	530	480	320	240	190	160																								
				FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																								
18	20	RPM	490	400	350	320	210	160	130	110																										
		FEED	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18	0.14~0.20	0.16~0.22	0.18~0.24																										
19	Malleable cast iron	25	RPM	610	500	440	400	270	200	160	130																									
			FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																									
20	20	RPM	490	400	350	320	210	160	130	110																										
		FEED	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18	0.14~0.20	0.16~0.22	0.18~0.24																										
N	21	Aluminum-wrought alloy	55	RPM	1350	1090	970	880	580	440	350	290																								
				FEED	0.16~0.22	0.18~0.24	0.20~0.28	0.20~0.30	0.28~0.38	0.32~0.42	0.36~0.46	0.40~0.50																								
	22	55	RPM	1350	1090	970	880	580	440	350	290																									
			FEED	0.16~0.22	0.18~0.24	0.20~0.28	0.20~0.30	0.28~0.38	0.32~0.42	0.36~0.46	0.40~0.50																									
	23	Aluminum-cast, alloyed	40	RPM	980	800	710	640	420	320	250	210																								
				FEED	0.16~0.22	0.18~0.24	0.20~0.28	0.20~0.30	0.28~0.38	0.32~0.42	0.36~0.46	0.40~0.50																								
	24																																			
	25																																			
												26																								
27	Copper and Copper Alloys (Bronze / Brass)																																			
											28																									
29	Non Metallic Materials	20	RPM	490	400	350	320	210	160	130											110															
			FEED	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	0.24~0.30	0.28~0.34	0.36~0.40																									
S	31	Heat Resistant Super Alloys																																		
												32																								
																				33																
																												34								
																																				35
	36	Titanium Alloys	10	RPM	240	200	180	160	110	80	60																									
				FEED	0.06~0.10	0.05~0.11	0.06~0.12	0.09~0.13	0.12~0.18	0.14~0.20	0.16~0.22	0.18~0.24																								
37																																				
											38	Hardened steel																								
39																																				
										40	Chilled Cast Iron																									
41	Hardened Cast Iron																																			

SELECTION GUIDE



SERIES	DL205	D1205	D1206
STANDARD	DIN345	DIN345	DIN341
LENGTH	JOBBER	JOBBER	LONG
SIZE MIN	D13.0	D5.0	D13.0
SIZE MAX	D30.0	D60.0	D30.0
PAGE	288	289	292
SURFACE TREATMENT	Bright	Steam Tempered	

# HSS & HSS-E MORSE TAPER SHANK DRILLS

Morse Taper Shank Drills for Wide Applications



Please visit [globalyg1.com/mat](http://globalyg1.com/mat) for material search

◎ : Excellent ○ : Good

Recommended cutting conditions : P.295

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment	HB	HRc	DL205	D1205	D1206
P	1	Non-alloy steel	About 0.15% C Annealed	125		◎	◎	◎
	2		About 0.45% C Annealed	190	13	◎	◎	◎
	3		About 0.45% C Quenched & Tempered	250	25	◎	◎	◎
	4		About 0.75% C Annealed	270	28	○	○	○
	5		About 0.75% C Quenched & Tempered	300	32			
	6	Low alloy steel	Annealed	180	10	◎	◎	◎
	7		Quenched & Tempered	275	29	○	○	○
	8		Quenched & Tempered	300	32	○	○	○
	9		Quenched & Tempered	350	38			
	10		High alloyed steel, and tool steel	Annealed	200	15	○	○
	11	Quenched & Tempered		325	35			
M	12	Stainless steel	Ferritic / Martensitic Annealed	200	15	◎	◎	◎
	13		Martensitic Quenched & Tempered	240	23	○	○	○
	14		Austenitic	180	10			
K	15	Grey cast iron	Pearlitic / ferritic	180	10	○	○	○
	16		Pearlitic (Martensitic)	260	26	○	○	○
	17	Nodular cast iron	Ferritic	160	3	○	○	○
	18		Pearlitic	250	25	○	○	○
	19		Ferritic	130		○	○	○
20	Malleable cast iron	Pearlitic	230	21	○	○	○	
N	21	Aluminum-wrought alloy	Not Curable	60		○	○	○
	22		Curable Hardened	100		○	○	○
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable	75		○	○	○
	24		≤ 12% Si, Curable Hardened	90				
	25		> 12% Si, Not Curable	130				
	26	Copper and Copper Alloys (Bronze / Brass)	Cutting Alloys, PB>1%	110				
	27		CuZn, CuSnZn (Brass)	90				
	28		CuSn, lead-free copper and electrolytic copper	100				
	29		Non Metallic Materials	Duroplastic, Fiber Reinforced Plastic Rubber, Wood, etc.			○	○
30								
S	31	Heat Resistant Super Alloys	Fe Based Annealed	200	15			
	32		Cured	280	30			
	33		Annealed	250	25			
	34		Ni or Co Based Cured	350	38			
	35		Cast	320	34			
	36	Titanium Alloys	Pure Titanium	400 Rm		○	○	○
	37		Alpha + Beta Alloys Hardened	1050 Rm				
H	38	Hardened steel	Hardened	550	55			
	39		Hardened	630	60			
	40	Chilled Cast Iron	Cast	400	42			
41	Hardened Cast Iron	Hardened	550	55				