

Y/G **STRAIGHT SHANK DRILLS**

DT600 SERIES **DT692** SERIES **DT693** SERIES

HSS-E, STRAIGHT SHANK TWIST DRILLS for DEEP HOLES **EXTRA LONG**
ÜBERLANG
EXTRA-LONGUE
EXTRA LUNGA

► **Surface treatment** : TiAIN coating on working area.
► **Application** : Drilling deep holes in non alloy steels, alloy steels, grey cast iron, malleable cast iron, special aluminum or magnesium alloys.
► **Verwendung** : Zum Bohren von legiertem und unlegiertem stahl, Grauguß, Temperguß, Sphäroguß, Druckguß, Alu-Legierungen kurzspanend, Bronze, Messing zäh, Neusilber.



DIN 1869/1 **DIN 1869/2** **DIN 1869/3** **HSS-E** **38°** **h8** **130°** **P.282**

► **DH100**
worm pattern drills

DT600 SERIES (DIN1869/1)

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
DT600020	2.0	85	125
DT600025	2.5	95	140
DT600030	3.0	100	150
DT600035	3.5	115	165
DT600040	4.0	120	175
DT600045	4.5	125	185
DT600050	5.0	135	195
DT600055	5.5	140	205
DT600060	6.0	140	205
DT600065	6.5	150	215
DT600070	7.0	155	225
DT600075	7.5	155	225
DT600080	8.0	165	240
DT600085	8.5	165	240
DT600090	9.0	175	250
DT600095	9.5	175	250
DT600100	10.0	185	265
DT600105	10.5	185	265

DT692 SERIES (DIN1869/2)

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
DT692030	3.0	130	190
DT692035	3.5	145	210
DT692040	4.0	150	220
DT692045	4.5	160	235
DT692050	5.0	170	245
DT692055	5.5	180	260
DT692060	6.0	180	260
DT692065	6.5	190	275
DT692070	7.0	200	290
DT692075	7.5	200	290
DT692080	8.0	210	305
DT692085	8.5	210	305
DT692090	9.0	220	320
DT692095	9.5	220	320
DT692100	10.0	235	340
DT692102	10.2	235	340

► TiN(DN600) and TiCN(DX600) are available on your request.

DT693 SERIES (DIN1869/3)

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
DT693040	4.0	190	280
DT693050	5.0	210	315
DT693060	6.0	225	330
DT693080	8.0	265	390
DT693100	10.0	295	430

◎ : Excellent ○ : Good

ISO	P										M				K								
Material Description	Non-alloy steel					Low alloy steel				High alloy steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25					
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230			
Recommended	◎	◎	◎	○		◎	○	○		○					○	○	○	○	○	○			
ISO	N										S										H		
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
HRc	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550		
HB											15	30	25	38	34			55	60	42	55		
Recommended																							

STRAIGHT
SHANK DRILLS

RECOMMENDED CUTTING CONDITIONS
EMPFOHLENE SCHNEIDPARAMETER

DT600, DT692, DT693 SERIES HSS-E, DH100 WORM PATTERN DRILLS (EXTRA LONG) RPM = rev./min. FEED = mm/rev.

ISO	VDI 3323	Material Description	Vc (m/min)	Parameter	Drill Diameter (mm)						
					2.0	3.0	4.0	6.0	8.0	10.0	13.0
P	1	Non-alloy steel	20	RPM FEED	3180 0.01~0.03	2120 0.03~0.05	1590 0.04~0.06	1060 0.05~0.08	800 0.08~0.11	640 0.09~0.13	490 0.10~0.16
	2		15	RPM FEED	2390 0.01~0.03	1590 0.03~0.05	1190 0.04~0.06	800 0.05~0.08	600 0.08~0.11	480 0.09~0.13	370 0.10~0.16
	3		10	RPM FEED	1590 0.01~0.03	1060 0.03~0.05	800 0.04~0.06	530 0.05~0.08	400 0.08~0.11	320 0.09~0.13	240 0.10~0.16
	4		10	RPM FEED	1590 0.01~0.02	1060 0.01~0.03	800 0.02~0.04	530 0.02~0.05	400 0.03~0.06	320 0.03~0.06	240 0.04~0.10
	5										
	6	Low alloy steel	15	RPM FEED	2390 0.01~0.03	1590 0.03~0.05	1190 0.04~0.06	800 0.05~0.08	600 0.08~0.11	480 0.09~0.13	370 0.10~0.16
	7		10	RPM FEED	1590 0.01~0.03	1060 0.03~0.05	800 0.04~0.06	530 0.05~0.08	400 0.08~0.11	320 0.09~0.13	240 0.10~0.16
	8		10	RPM FEED	1590 0.01~0.02	1060 0.01~0.03	800 0.02~0.04	530 0.02~0.05	400 0.03~0.06	320 0.03~0.06	240 0.04~0.10
	9										
	10	High alloyed steel, and tool steel	5	RPM FEED	800 0.01~0.03	530 0.03~0.05	400 0.04~0.06	270 0.05~0.08	200 0.08~0.11	160 0.09~0.13	120 0.10~0.16
	11										
M	12	Stainless steel									
	13										
	14										
K	15	Grey cast iron	20	RPM FEED	3180 0.01~0.03	2120 0.03~0.05	1590 0.04~0.06	1060 0.05~0.08	800 0.08~0.11	640 0.09~0.13	490 0.10~0.16
	16		15	RPM FEED	2390 0.01~0.02	1590 0.01~0.03	1190 0.02~0.04	800 0.02~0.05	600 0.03~0.06	480 0.03~0.06	370 0.04~0.10
	17	Nodular cast iron	20	RPM FEED	3180 0.01~0.03	2120 0.03~0.05	1590 0.04~0.06	1060 0.05~0.08	800 0.08~0.11	640 0.09~0.13	490 0.10~0.16
	18		10	RPM FEED	1590 0.01~0.02	1060 0.01~0.03	800 0.02~0.04	530 0.02~0.05	400 0.03~0.06	320 0.03~0.06	240 0.04~0.10
	19	Malleable cast iron	15	RPM FEED	2390 0.01~0.03	1590 0.03~0.05	1190 0.04~0.06	800 0.05~0.08	600 0.08~0.11	480 0.09~0.13	370 0.10~0.16
	20		10	RPM FEED	1590 0.01~0.02	1060 0.01~0.03	800 0.02~0.04	530 0.02~0.05	400 0.03~0.06	320 0.03~0.06	240 0.04~0.10
N	21	Aluminum-wrought alloy									
	22										
	23	Aluminum-cast, alloyed									
	24										
	25										
	26	Copper and Copper Alloys (Bronze / Brass)									
	27										
	28										
	29	Non Metallic Materials									
	30										
S	31	Heat Resistant Super Alloys									
	32										
	33										
	34										
	35	Titanium Alloys									
	36										
	37										
H	38	Hardened steel									
	39										
	40	Chilled Cast Iron									
	41	Hardened Cast Iron									

SELECTION GUIDE



SERIES

DH100
DL510

DH100
DL508

DH100
DL509

STANDARD

DIN1897

DIN338

DIN340

LENGTH

STUB

JOBBER

LONG

SIZE MIN

D2.0

D2.0

D2.0

SIZE MAX

D20.0

D16.0

D12.0

PAGE

263

265

267

SURFACE TREATMENT

Bright

HSS-E
STRAIGHT SHANK
DRILLS

For General Purpose (Soft & Tough Materials)



Please visit
globalyg1.com/mat
for material search

◎ : Excellent ○ : Good

Recommended cutting conditions : P.276



ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment		HB	HRc			
P	1	Non-alloy steel	About 0.15% C	Annealed	125		◎	◎	◎
	2		About 0.45% C	Annealed	190	13	◎	◎	◎
	3		About 0.45% C	Quenched & Tempered	250	25	◎	◎	◎
	4		About 0.75% C	Annealed	270	28	○	○	○
	5		About 0.75% C	Quenched & Tempered	300	32			
	6	Low alloy steel		Annealed	180	10	◎	◎	◎
	7			Quenched & Tempered	275	29	○	○	○
	8			Quenched & Tempered	300	32	○	○	○
	9			Quenched & Tempered	350	38			
	10	High alloyed steel, and tool steel		Annealed	200	15	○	○	○
	11			Quenched & Tempered	325	35			
M	12	Stainless steel	Ferritic / Martensitic	Annealed	200	15			
	13		Martensitic	Quenched & Tempered	240	23			
	14		Austenitic		180	10			
K	15	Grey cast iron	Pearlitic / ferritic		180	10	○	○	○
	16		Pearlitic (Martensitic)		260	26	○	○	○
	17	Nodular cast iron	Ferritic		160	3	○	○	○
	18		Pearlitic		250	25	○	○	○
	19	Malleable cast iron	Ferritic		130		○	○	○
	20		Pearlitic		230	21	○	○	○
N	21	Aluminum-wrought alloy	Not Curable		60				
	22		Curable	Hardened	100				
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable		75				
	24		≤ 12% Si, Curable	Hardened	90				
	25		> 12% Si, Not Curable		130				
	26	Copper and Copper Alloys (Bronze / Brass)	Cutting Alloys, PB>1%		110				
	27		CuZn, CuSnZn (Brass)		90				
	28		CuSn, lead-free copper and electrolytic copper		100				
	29		Duroplastic, Fiber Reinforced Plastic						
	30	Non Metallic Materials	Rubber, Wood, etc.						
S	31	Heat Resistant Super Alloys	Fe Based	Annealed	200	15			
	32			Cured	280	30			
	33			Annealed	250	25			
	34		Ni or Co Based	Cured	350	38			
	35			Cast	320	34			
	36	Titanium Alloys	Pure Titanium		400 Rm				
	37		Alpha + Beta Alloys	Hardened	1050 Rm				
H	38	Hardened steel		Hardened	550	55			
	39			Hardened	630	60			
	40	Chilled Cast Iron		Cast	400	42			
	41	Hardened Cast Iron		Hardened	550	55			

i-ONE
DRILLSi-DREAM
DRILLS

DREAM
DRILLS
-GENERAL

DREAM
DRILLS
-HIGH FEED

DREAM
DRILLS
-FLAT BOTTOM

DREAM
DRILLS
-INOX

DREAM
DRILLS
-ALU

DREAM
DRILLS
-CFRP

DREAM
DRILLS
-MQL

DREAM DRILLS for HIGH HARDENED STEELS

GENERAL CARBIDE DRILLS

MULTI-1 DRILLS

HPD
DRILLS

GOLD-P
DRILLS

SUPER-GP
DRILLS

STRAIGHT SHANK DRILLS

TAPER SHANK DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

SPADE
DRILLS

REAMERS

COUNTER SINKS

COUNTERBORES

TECHNICAL DATA