



CARBIDE, 4 FLUTE SHORT LENGTH

- VOLLHARTMETALL, 4 SCHNEIDEN KURZ
- ⊖ Fraise carbure, 4 dents, courte
- ⊖ 4 TAGLIENTI, SERIE CORTA

- ▶ Designed to machine tool steels, alloy steels, mold steels and other hardened materials.
- ▶ 4 flute allows for better workpiece finishes.
- ▶ Increased Productivity.

- ▶ Zur Bearbeitung: Werkzeugstählen, Legierten Stählen, Stahlguß und gehärteten Stählen.
- ▶ 4 Schneiden erzeugen eine bessere Oberfläche des Werkstücks.
- ▶ Höhere Produktivität.



CARBIDE
4
30°
PLAIN
P.390

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
GM811020	2.0	4	6	40
GM811901	2.0	6	6	40
GM811025	2.5	4	8	40
GM811902	2.5	6	8	40
GM811030	3.0	6	8	45
GM811035	3.5	6	10	45
GM811040	4.0	6	11	45
GM811045	4.5	6	11	45
GM811050	5.0	6	13	50
GM811060	6.0	6	13	50
GM811080	8.0	8	19	60
GM811100	10.0	10	22	70
GM811120	12.0	12	26	75
GM811140	14.0	14	26	85
GM811160	16.0	16	32	100
GM811200	20.0	20	38	105
GM811250	25.0	25	45	120

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ - 0.03	h5

◎ : Excellent ○ : Good

ISO Material Description	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc																				
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommend	○	○	○	◎	◎	○	◎	◎	◎	○	◎	○	○	○	○	○	○	○	○	○

ISO Material Description	N					S										H					
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc																					
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend																		○	◎	○	○


YG X-POWER PRO END MILLS

**RECOMMENDED CUTTING CONDITIONS
EMPFOHLENE SCHNEIDPARAMETER**

GM811 SERIES 4 FLUTE - SIDE CUTTING

Vc = m/min.
fz = mm/tooth
RPM = rev./min.
FEED = mm/min.

ISO	VDI 3323	Material Description	Ae	Ap	Parameter	Diameter (Ø)										
						2.0	3.0	4.0	5.0	6.0	8.0	10.0	12.0	16.0	20.0	25.0
P	1-4	Non-alloy steel	0.05D	1.0D	Vc	80	95	105	110	115	120	115	115	125	120	120
					fz	0.006	0.009	0.019	0.024	0.03	0.042	0.047	0.047	0.047	0.048	0.046
	RPM				12732	10080	8356	7003	6101	4775	3661	3050	2487	1910	1528	
	FEED				306	363	635	672	732	802	688	573	468	367	281	
	Vc				55	60	65	65	70	70	70	70	75	75	75	
	fz				0.006	0.009	0.019	0.024	0.031	0.038	0.037	0.037	0.037	0.038	0.039	
	5	Low alloy steel	0.05D	1.0D	RPM	8754	6366	5173	4138	3714	2785	2228	1857	1492	1194	955
					FEED	210	229	393	397	460	423	330	275	221	181	149
	Vc				80	95	105	110	115	120	115	115	125	120	120	
	fz				0.006	0.009	0.019	0.024	0.03	0.042	0.047	0.047	0.047	0.048	0.046	
	RPM				12732	10080	8356	7003	6101	4775	3661	3050	2487	1910	1528	
	FEED				306	363	635	672	732	802	688	573	468	367	281	
6-7	High alloyed steel, and tool steel	0.05D	1.0D	Vc	55	60	65	65	70	70	70	70	75	75	75	
				fz	0.006	0.009	0.019	0.024	0.031	0.038	0.037	0.037	0.037	0.038	0.039	
RPM				8754	6366	5173	4138	3714	2785	2228	1857	1492	1194	955		
FEED				210	229	393	397	460	423	330	275	221	181	149		
Vc				80	95	105	110	115	120	115	115	125	120	120		
fz				0.006	0.009	0.019	0.024	0.03	0.042	0.047	0.047	0.047	0.048	0.046		
8-9	High alloyed steel, and tool steel	0.05D	1.0D	RPM	12732	10080	8356	7003	6101	4775	3661	3050	2487	1910	1528	
				FEED	306	363	635	672	732	802	688	573	468	367	281	
Vc				55	60	65	65	70	70	70	70	75	75	75		
fz				0.006	0.009	0.019	0.024	0.031	0.038	0.037	0.037	0.037	0.038	0.039		
RPM				8754	6366	5173	4138	3714	2785	2228	1857	1492	1194	955		
FEED				210	229	393	397	460	423	330	275	221	181	149		
10	Stainless steel	0.05D	1.0D	Vc	80	95	105	110	115	120	115	115	125	120	120	
				fz	0.006	0.009	0.019	0.024	0.03	0.042	0.047	0.047	0.047	0.048	0.046	
RPM				12732	10080	8356	7003	6101	4775	3661	3050	2487	1910	1528		
FEED				306	363	635	672	732	802	688	573	468	367	281		
Vc				55	60	65	65	70	70	70	70	75	75	75		
fz				0.006	0.009	0.019	0.024	0.031	0.038	0.037	0.037	0.037	0.038	0.039		
11.1 - 11.2	Stainless steel	0.05D	1.0D	RPM	8754	6366	5173	4138	3714	2785	2228	1857	1492	1194	955	
				FEED	210	229	393	397	460	423	330	275	221	181	149	
Vc				45	50	55	55	60	60	60	60	65	60	60		
fz				0.005	0.009	0.018	0.024	0.029	0.041	0.045	0.044	0.046	0.045	0.044		
RPM				7162	5305	4377	3501	3183	2387	1910	1459	1194	955	764		
FEED				143	191	315	336	369	392	344	257	220	172	134		
M	Grey cast iron Nodular cast iron Malleable cast iron	0.05D	1.0D	Vc	80	95	105	110	115	120	115	115	125	120	120	
				fz	0.006	0.009	0.019	0.024	0.03	0.042	0.047	0.047	0.047	0.048	0.046	
RPM				12732	10080	8356	7003	6101	4775	3661	3050	2487	1910	1528		
FEED				306	363	635	672	732	802	688	573	468	367	281		
Vc				35	35	40	40	40	45	50	50	50	50	45		
fz				0.002	0.004	0.005	0.008	0.010	0.017	0.016	0.017	0.016	0.015	0.015		
K	Hardened steel	0.05D	1.0D	RPM	5570	3714	3183	2546	2122	1790	1592	1326	995	796	573	
				FEED	45	59	64	81	85	122	102	90	64	48	34	
Vc				55	60	65	65	70	70	70	70	75	75	75		
fz				0.006	0.009	0.019	0.024	0.031	0.038	0.037	0.037	0.037	0.038	0.039		
RPM				8754	6366	5173	4138	3714	2785	2228	1857	1492	1194	955		
FEED				210	229	393	397	460	423	330	275	221	181	149		
H	Chilled Cast Iron	0.05D	1.0D	Vc	35	35	40	40	40	45	50	50	50	50	45	
				fz	0.002	0.004	0.005	0.008	0.010	0.017	0.016	0.017	0.016	0.015	0.015	
RPM				5570	3714	3183	2546	2122	1790	1592	1326	995	796	573		
FEED				45	59	64	81	85	122	102	90	64	48	34		
Vc				55	60	65	65	70	70	70	70	75	75	75		
fz				0.006	0.009	0.019	0.024	0.031	0.038	0.037	0.037	0.037	0.038	0.039		
40	Hardened Cast Iron	0.05D	1.0D	RPM	8754	6366	5173	4138	3714	2785	2228	1857	1492	1194	955	
				FEED	210	229	393	397	460	423	330	275	221	181	149	
Vc				35	35	40	40	40	45	50	50	50	50	45		
fz				0.002	0.004	0.005	0.008	0.010	0.017	0.016	0.017	0.016	0.015	0.015		
RPM				5570	3714	3183	2546	2122	1790	1592	1326	995	796	573		
FEED				45	59	64	81	85	122	102	90	64	48	34		



SELECTION GUIDE



SERIES	GM876	GM813	GM886	GM902
FLUTE	2	2	2	2
HELIX ANGLE	30°	30°	30°	30°
CUTTING EDGE SHAPE	BALL NOSE	BALL NOSE	BALL NOSE	BALL NOSE
SIZE MIN	R0.5	R0.5	R0.25	R0.5
SIZE MAX	R8.0	R10.0	R3.0	R4.0
PAGE	350	351	352	354

SOLID CARBIDE

X-POWER PRO

END MILLS

for Pre-Hardened Steels up to HRc55, Mold & Die, Dry & Wet Cutting

SHORT LENGTH	LONG LENGTH	RIB PROCESSING	TAPER NECK
Y-Coating	Y-Coating	Y-Coating	Y-Coating



Please visit globalyg1.com/mat for material search

◎: Excellent ○: Good

Recommended cutting conditions : P 372

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment	HB	HRc					
P	1	Non-alloy steel	About 0.15% C Annealed	125		○	○	○	○	
	2		About 0.45% C Annealed	190	13	○	○	○	○	
	3		About 0.45% C Quenched & Tempered	250	25	○	○	○	○	
	4		About 0.75% C Annealed	270	28	◎	◎	◎	○	
	5		About 0.75% C Quenched & Tempered	300	32	◎	◎	◎	○	
	6	Low alloy steel	Annealed	180	10	○	○	○	○	
	7		Quenched & Tempered	275	29	◎	◎	◎	○	
	8		Quenched & Tempered	300	32	◎	◎	◎	◎	
	9		Quenched & Tempered	350	38	◎	◎	◎	◎	
	10		High alloyed steel, and tool steel	Annealed	200	15	○	○	○	○
	11			Quenched & Tempered	325	35	◎	◎	◎	◎
M	12	Stainless steel	Ferritic / Martensitic Annealed	200	15					
	13		Martensitic Quenched & Tempered	240	23					
	14		Austenitic	180	10					
K	15	Grey cast iron	Pearlitic / ferritic	180	10	○	○	○		
	16		Pearlitic (Martensitic)	260	26	○	○	○		
	17	Nodular cast iron	Ferritic	160	3	○	○	○		
	18		Pearlitic	250	25	○	○	○		
	19		Ferritic	130		○	○	○		
20	Malleable cast iron	Pearlitic	230	21	○	○	○			
N	21	Aluminum-wrought alloy	Not Curable	60						
	22		Curable Hardened	100						
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable	75						
	24		≤ 12% Si, Curable Hardened	90						
	25		> 12% Si, Not Curable	130						
	26		Cutting Alloys, PB>1%	110						
	27	Copper and Copper Alloys (Bronze / Brass)	CuZn, CuSnZn (Brass)	90						
	28		CuSn, lead-free copper and electrolytic copper	100						
	29	Non Metallic Materials	Duroplastic, Fiber Reinforced Plastic							
	30		Rubber, Wood, etc.							
S	31	Heat Resistant Super Alloys	Fe Based Annealed	200	15					
	32		Cured	280	30					
	33		Annealed	250	25					
	34		Ni or Co Based Cured	350	38					
	35		Cast	320	34					
	36	Titanium Alloys	Pure Titanium	400 Rm						
	37		Alpha + Beta Alloys Hardened	1050 Rm						
H	38	Hardened steel	Hardened	550	55	○	○	○	○	
	39		Hardened	630	60	○	○	○	○	
	40	Chilled Cast Iron	Cast	400	42	◎	◎	◎	◎	
	41	Hardened Cast Iron	Hardened	550	55	○	○	○	○	

GM815	GM818	GM8A1	GM839	GM819	GM810	GM883	GM895	GM811	GM817	GM812	GM834	GM814
4	2	2	4	4	2	2	3	4	4	6&8	6	3&4
30°	30°	30°	30°	30°	30°	30°	38°	30°	30°	45°	45°	20°
BALL NOSE	CORNER RADIUS	CORNER RADIUS	CORNER RADIUS	CORNER RADIUS	SQUARE	SQUARE	SQUARE	SQUARE	SQUARE	SQUARE	SQUARE	ROUGHING
R1.0	D4.0	D1.0	D2.0	D3.0	D0.4	D0.4	D1.0	D2.0	D2.0	D6.0	D6.0	D6.0
R8.0	D12.0	D6.0	D12.0	D20.0	D20.0	D6.0	D16.0	D25.0	D20.0	D20.0	D25.0	D20.0
355	356	357	359	360	361	363	366	367	368	369	370	371
LONG LENGTH	LONG LENGTH	RIB PROCESSING	STUB LENGTH	LONG LENGTH	SHORT LENGTH	RIB PROCESSING	SHORT LENGTH	SHORT LENGTH	LONG LENGTH	LONG LENGTH	EXTRA LONG LENGTH	LONG LENGTH
Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating	Y-Coating

○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎
◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎
○	○	○	○	○	○	○	○	○	○	○	○	○
◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎
◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎
○	○	○	○	○	○	○	○	○	○	○	○	○
◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎
				○	○	○	○	○	○	○	○	○
				○	○	○	○	○	○	○	○	○
				○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○
◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎
○	○	○	○	○	○	○	○	○	○	○	○	○

HSS

CBN END MILLS

i-Xmill END MILLS

i-SMART MODULAR END MILLS

X5070 END MILLS

4G MILL END MILLS

X-POWER PRO END MILLS

TitaNox-POWER END MILLS

JET-POWER END MILLS

V7 PLUS END MILLS

ALU-POWER HPC END MILLS

ALU-POWER END MILLS

D-POWER GRAPHITE END MILLS

D-POWER CFRP END MILLS

ROUTERS

CRX S END MILLS

K-2 END MILLS

ONLY ONE COATED PM60 END MILLS

TANK-POWER END MILLS

GENERAL HSS END MILLS

MILLING CUTTERS

TECHNICAL DATA