



Chamfer milling

CMZ01 Kr: 30°






Straight shank

Article	*	Stock	Dimensions [mm]				Teeth	kg	Inserts
			ØD	ød	L ₁	L			
CMZ01-012-G20-SP12-01		●	12	20	40	100	1	0.2	 SPMT1204
CMZ01-025-G25-SP12-02		●	25	25	40	120	2	0.8	
CMZ01-032-G32-SP12-03		●	32	32	40	180	3	1.1	

● Ex stock ○ On demand

* With internal cooling

Spare parts




	Insert	SPMT1204	
	ØD	12-32	
 Screw (insert)		I43M5*11	
 Wrench (insert)		WT20IS	

System code > B22

Grade selection > B20



Technical info > B447

Cutting data > B216

-  Ideal machining conditions
-  Normal machining conditions
-  Unfavourable machining conditions

SPMT	L	I.C	S	d
12 04	12.7	12.7	4.76	5.5

Milling inserts

SP** milling insert		HC ¹ (CVD)						HC ¹ (PVD)						HT	HC ²	HW							
	P																						
	M																						
	K																						
	N																						
	S																						
	H																						
ISO	r	YBC302	YBC301	YBC401	YBM253	YBM251	YBM351	YBD152	YBD252	YBG101	YBG102	YB9320	YBG205	YBG202	YBG212	YBG302	YBG152	YBG252	YNG151	YNG151C	YD101	YD201	
 SPMT120408	0.8	○	●	○	●	●										●							

● Ex stock ○ On demand

HC¹ Coated carbide
 HT Uncoated cermet
 HC² Coated cermet
 HW Uncoated carbide

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index

System code > B22

Grade selection > B20

Technical info > B447

Cutting data > B216



FM E 03 100 – B32 S – P 12 – 06 (L) (C)

1 2 3 4 5 6 7 8 9 10 11

Type		Entering angle		Serial no.	Nominal diameter [mm]	
Code	Description	A	E		Code	Description
BM	Profile milling				025	25
CM	Chamfer milling				050	50
EM	Square shoulder milling				160	160
FM	Face milling				315	315
HM	Helical milling				...	
SM	Slot milling					
TM	T-slot milling					
XM	Special					

Type and size of tool holders			
Code	Type	Code	Type
A	<p>Nominal diameter Ø50 – 80 mm</p>	B	<p>Nominal diameter Ø100 – 160 mm</p>
C	<p>Nominal diameter Ø200 – 250 mm</p>	D	<p>Nominal diameter Ø315 mm</p>
G	Straight shank	XP	Weldon shank
K	Bore with keyway		

5

With respect to mounting please adhere to the information provided by the tool holder manufacturer.

Insert shape	
A	C
H	L
M	O
P	R
S	T
W	X Special
Z	Special

6

Clearance angle	
B	C
D	E
F	N
P	

7

Cutting edge length l [mm]	
Insert shape	
A	C, M
H, O, P	L
R	S
T	W

8

No. of teeth

9

Cutting direction	
Code	Description
L	Left

10

With inner cooling

11



Tools with B coupling and inner coolant supply require the following spare parts:



Coolant clamp screw



Coolant shower plate



Spare parts (B coupling with inner coolant supply)

		B27	B32	B40	B40
	∅	80	100	125	160
	Coolant clamp screw	LDB27C	LDB32C	LDB40C	LDB40C
	Coolant shower plate	B27-002-CP	B32-002-CP	B40-002-CP	B40-003-CP

When purchasing tools with inner coolant supply and B coupling these spare parts are included in delivery.

A

Turning

B

Milling

C

Drilling

D












Technical Information

E








Index

S P K N 12 04 ED T21K R – DM





1 2 3 4 5 6 7 8 9 10

Insert shape	
A 	C 
H 	L 
M 	O 
P 	R 
S 	T 
W 	X Special
Z Special	















1

Clearance angle	
B 	C 
D 	E 
F 	N 
P 	









2

Tolerance class			
			
Code	I.C [mm]	m [mm]	S [mm]
A	±0.025	±0.005	±0.025
C	±0.025	±0.013	±0.025
E	±0.025	±0.025	±0.025
F	±0.013	±0.005	±0.025
G	±0.025	±0.025	±0.130
H	±0.013	±0.013	±0.025
J	±0.05–0.13	±0.005	±0.025
K	±0.05–0.13	±0.013	±0.025
L	±0.05–0.13	±0.025	±0.025
M	±0.05–0.13	±0.08–0.18	±0.130
N	±0.05–0.13	±0.08–0.18	±0.025
U	±0.08–0.25	±0.13–0.38	±0.130



3

Fastening features (metric)	
Insert shape	
A 	B 
C 	F 
G 	H 
J 	M 
N 	Q 
R 	T 
U 	W 
X Special	



4

Cutting edge length l [mm]	
Insert shape	
	
A	C, M
	
H, O, P	L
	
R	S
	
T	W








5

Insert thickness S [mm]			
			
Code	S	Code	S
00	0.79	05	5.56
T0	0.99	T5	5.95
01	1.59	06	6.35
T1	1.98	T6	6.75
02	2.38	07	7.94
T2	2.58	09	9.52
03	3.18	T9	9.72
T3	3.97	11	11.11
04	4.76	12	12.70
T4	4.96		

6

Angle			
			
Code	Kr	Code	an
A	45°	A	3°
D	60°	B	5°
E	75°	C	7°
F	85°	D	15°
P	90°	E	20°
Z	Special	F	25°
		G	30°
		N	0°
		P	11°
		Z	Special

7

Chamfer							
Code	Type	Code	Angle	Code	Width [mm]	Code	Position
F		0	5°	0	0.10	K	
E		1	10°	1	0.15		
T		2	15°	2	0.20		
S		3	20°	3	0.25		
		4	25°	4	0.30		
		5	30°	5	0.35		
				6	0.40	W	
				7	0.45		
						-	

8

Cutting direction	
Code	Description
R	Right
L	Left
N	Right and left

9

Chip breaker overview
(on page B16)

10

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index

Guide for recommended cutting data – indexable milling

Indexable milling - group 1 (FMA07/11/12, FMD02, EMP09/13)

Material group	Composition / structure / heat treatment	Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]								
				HC (VDI)				YBD				
				YBC302		YBC401		YBD152		YBD252		
a_p / D		a_p / D		a_p / D		a_p / D						
1/1 3/4		1/5		1/1 3/4		1/5		1/1 3/4		1/5		
P Unalloyed steel	ca. 0,15 % C	annealed	125	1	260	300	225	280				
	ca. 0,45 % C	annealed	190	2	225	255	195	225				
	ca. 0,45 % C	tempered	250	3	210	240	180	210				
	ca. 0,75 % C	annealed	270	4	185	210	160	185				
	ca. 0,75 % C	tempered	300	5	170	195	150	170				
P Low-alloyed steel		annealed	180	6	225	255	195	225				
		tempered	275	7	185	210	160	185				
		tempered	300	8	170	195	150	170				
		tempered	350	9	145	165	125	145				
P High-alloyed steel and high-alloyed tool steel		annealed	200	10	130	150	115	130				
		hardened and tempered	325	11	95	105	80	95				
M Stainless steel	ferritic/martensitic	annealed	200	12								
	martensitic	tempered	240	13								
	austenitic	quench hardened	180	14								
	austenitic-ferritic		230	15								
K Grey cast iron	perlitic/ferritic		180	16				370	430	320	370	
	perlitic (martensitic)		260	17				220	255	150	220	
	ferritic		160	18				255	295	220	255	
	perlitic		250	19				170	200	145	170	
K Cast iron with spheroidal graphite	ferritic		130	20				305	355	265	305	
	perlitic		230	21				205	240	175	205	
N Malleable cast iron	Aluminium wrought alloys	cannot be hardened	60	22								
		hardenable	100	23								
	Cast aluminium alloys	≤ 12% Si, cannot be hardened	75	24								
		≤ 12% Si, hardenable	90	25								
N Copper and copper alloys (bronze/brass)	> 12% Si, cannot be hardened	130	26									
	machining steel, PB > 1%		110	27								
			90	28								
S Heat-resistant alloys	Fe-based alloys	annealed	200	30								
		hardened	280	31								
	Ni or Co base	annealed	250	32								
		cast	320	34								
S Titanium alloys	pure titanium	R_m 400	35									
	α and β alloys	hardened	R_m 1050	36								
H Hardened steel		hardened and tempered	55 HRC	37								
		hardened and tempered	60 HRC	38								
	Hard cast iron	cast	400	39								
X Non-metallic materials	Hardened cast iron	hardened and tempered	55 HRC	40								
	Thermoplasts			41								
	Thermosetting plastics			42								
	Plastic, glass-fibre reinforced GFRP			43								
	Plastic, carbon fibre reinforced CFRP			44								
X Graphite				45								
	Wood			46								

Note: The given cutting values are guide values, which were determined under ideal conditions. The values have to be adapted in individual cases. Feed rate recommendations on page B240. For examples of material for cutting tool groups view page D22.

Recommend feed rate

Indexable milling – group 1 (FMA07/11/12, FMD02, EMP09/13)

5	Material group	Feed rate per cutting edge (mm)																	
		EMP09			EMP13			FMA07			FMA07			FMA11					
		LNKT12			ANGX15			ONHU06			ONHU08			SNEG12					
		Application																	
	F	M	R	F	M	R	F	M	R	F	M	R	F	M	R				
P	Unalloyed steel	0,25	0,50		0,23			0,25			0,19	0,23		0,19	0,23		0,20	0,23	
	Low-alloyed steel	0,23	0,47		0,22			0,23			0,17	0,22		0,17	0,22		0,19	0,21	
	High-alloyed steel and high-alloyed tool steel	0,22	0,44		0,20			0,22			0,16	0,20		0,16	0,20		0,18	0,20	
M	Stainless steel		0,18	0,35													0,14	0,16	
K	Grey cast iron	0,28	0,55		0,26			0,28			0,20	0,26		0,20	0,26		0,22	0,25	
	Cast iron with spheroidal graphite	0,25	0,50		0,23			0,25			0,19	0,23		0,19	0,23		0,20	0,23	
	Malleable cast iron	0,25	0,50		0,23			0,25			0,19	0,23		0,19	0,23		0,20	0,23	
N	Aluminium wrought alloys				0,20			0,21											
	Aluminium-Gusslegierungen				0,20			0,21											
	Copper and copper alloys (bronze/brass)				0,18			0,19											
S	Heat-resistant alloys																		
	Titanium alloys																		
H	Hardened steel																		
	Hard cast iron																		
	Hardened cast iron																		
X	Non-metallic materials																		

1. Select the appropriate product family/cutting data group.
2. Select the used grade.
3. Determine the immersion.
4. Select the used material and read the cutting speed.
5. Please have a look at the detached feed rate recommendations.
6. Select the used tool, the machining mode and the used material.

A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index

Indexable milling – group 4 (BMR01/02/03/04, TMP01,CMZ01,CMA01,CMD01)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]							
						HC (CVD)							
						YBC302			YBC401				
						a_e / D			a_e / D				
1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20								
P	Unalloyed steel	ca. 0,15 % C	annealed	125	1	235	275	360	200	230	300		
		ca. 0,45 % C	annealed	190	2	200	235	310	170	200	260		
		ca. 0,45 % C	tempered	250	3	190	220	290	160	185	245		
		ca. 0,75 % C	annealed	270	4	165	195	255	140	165	215		
		ca. 0,75 % C	tempered	300	5	155	180	235	130	150	195		
	Low-alloyed steel		annealed	180	6	200	235	310	170	200	260		
			tempered	275	7	165	195	255	140	165	215		
			tempered	300	8	155	180	235	130	150	195		
			tempered	350	9	130	155	205	110	130	170		
		High-alloyed steel and high-alloyed tool steel		annealed	200	10	120	140	185	100	115	150	
	hardened and tempered		325	11	85	100	130	70	85	115			
M	Stainless steel	ferritic/martensitic	annealed	200	12								
		martensitic	tempered	240	13								
		austenitic	quench hardened	180	14								
		austenitic-ferritic		230	15								
K	Grey cast iron	perlitic/ferritic		180	16								
		perlitic (martensitic)		260	17								
	Cast iron with spheroidal graphite	ferritic		160	18								
		perlitic		250	19								
	Malleable cast iron	ferritic		130	20								
		perlitic		230	21								
N	Aluminium wrought alloys	cannot be hardened		60	22								
		hardenable	hardened	100	23								
	Cast aluminium alloys	$\leq 12\%$ Si, cannot be hardened		75	24								
		$\leq 12\%$ Si, hardenable	hardened	90	25								
		$> 12\%$ Si, cannot be hardened		130	26								
	Copper and copper alloys (bronze/brass)	machining steel, PB> 1%			110	27							
		CuZn, CuSnZn			90	28							
CuSn, Pb-free copper, electrolytic copper			100	29									
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30								
			hardened	280	31								
		Ni or Co base	annealed	250	32								
			hardened	350	33								
	cast	320	34										
Titanium alloys	pure titanium		R_m 400	35									
α and β alloys	hardened		R_m 1050	36									
H	Hardened steel		hardened and tempered	55 HRC	37								
			hardened and tempered	60 HRC	38								
	Hard cast iron		cast	400	39								
Hardened cast iron		hardened and tempered	55 HRC	40									
X	Non-metallic materials	Thermoplasts			41								
		Thermosetting plastics			42								
		Plastic, glass-fibre reinforced GFRP			43								
		Plastic, carbon fibre reinforced CFRP			44								
		Graphite			45								
		Wood			46								

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B240.
 For examples of material for cutting tool groups view page D22.

Starting values for cutting speed v_c [m/min]																						
HC (CVD)									HC (PVD)													
YBD152			YBD252			YBM253			YBG102			YBG152			YB9320			YBG205				
a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D			a_e / D				
1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20		
								235	275	360	245	285	375	230	265	345	220	255	335	210	245	320
								200	235	310	210	245	320	200	230	300	190	220	290	180	210	275
								190	220	290	200	230	300	185	215	280	180	205	270	170	200	260
								165	195	255	175	200	260	165	190	250	155	180	235	150	175	230
								155	180	235	160	190	250	150	175	230	145	170	225	140	160	210
								200	235	310	210	245	320	200	230	300	190	220	290	180	210	275
								165	195	255	175	200	260	165	190	250	155	180	235	150	175	230
								155	180	235	160	190	250	150	175	230	145	170	225	140	160	210
								130	155	205	135	160	210	130	150	195	125	145	190	120	135	180
								120	140	185	125	145	190	115	135	180	110	130	170	105	125	165
								85	100	130	90	100	130	85	95	125	80	90	120	75	90	120
								120	140	180	125	145	190	115	135	175	110	130	170	105	125	160
								100	120	155	105	120	160	100	115	145	95	110	145	90	105	135
								125	150	195	130	155	200	125	145	185	120	140	180	115	130	170
								100	120	155	105	120	160	100	115	145	95	110	145	90	105	135
	300	345	450	260	300	390					270	315	410	255	295	385	245	285	375	235	275	360
	180	210	275	155	180	235					160	190	250	150	175	230	145	170	225	140	160	210
	210	245	320	180	210	275					185	215	280	175	200	260	165	195	255	160	185	245
	140	165	215	120	140	185					125	145	190	115	135	180	110	130	170	105	125	165
	250	290	380	215	250	325					225	260	340	210	240	315	200	230	300	190	225	295
	170	200	260	145	165	215					150	175	230	140	160	210	135	155	205	130	150	195

HC Coated carbide
 HT Uncoated carbide, main component (TiC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index

Indexable milling – group 4 (BMR01/02/03/04, TMP01, CMZ01, CMA01, CMD01)

	Material group	Composition / structure / heat treatment		Brinell hardness HB	Machining group	Starting values for cutting speed v_c [m/min]					
						HC (PVD)					
						YBG212			YBG252		
						a_e / D			a_e / D		
	1/1 3/4	1/5	1/20	1/1 3/4	1/5	1/20					
P	Unalloyed steel	ca. 0,15 % C	annealed	125	1	215	250	325	205	240	315
		ca. 0,45 % C	annealed	190	2	185	215	280	175	205	270
		ca. 0,45 % C	tempered	250	3	175	200	260	165	195	255
		ca. 0,75 % C	annealed	270	4	155	175	230	145	170	225
		ca. 0,75 % C	tempered	300	5	140	165	215	135	160	210
	Low-alloyed steel		annealed	180	6	185	215	280	175	205	270
			tempered	275	7	155	175	230	145	170	225
			tempered	300	8	140	165	215	135	160	210
			tempered	350	9	120	140	185	115	135	180
		High-alloyed steel and high-alloyed tool steel		annealed	200	10	110	125	165	105	120
	hardened and tempered		325	11	80	90	120	75	85	115	
M	Stainless steel	ferritic/martensitic	annealed	200	12	110	125	165	105	120	160
		martensitic	tempered	240	13	95	105	140	90	105	135
		austenitic	quench hardened	180	14	115	135	175	110	130	170
		austenitic-ferritic		230	15	95	105	140	90	105	135
K	Grey cast iron	perlitic/ferritic		180	16	240	280	365	230	265	345
		perlitic (martensitic)		260	17	140	165	215	135	160	210
	Cast iron with spheroidal graphite	ferritic		160	18	165	190	250	155	180	235
		perlitic		250	19	110	125	165	105	120	160
	Malleable cast iron	ferritic		130	20	195	225	295	185	220	290
		perlitic		230	21	130	150	195	125	145	190
N	Aluminium wrought alloys	cannot be hardened		60	22						
		hardenable	hardened	100	23						
	Cast aluminium alloys	$\leq 12\%$ Si, cannot be hardened		75	24						
		$\leq 12\%$ Si, hardenable	hardened	90	25						
		$> 12\%$ Si, cannot be hardened		130	26						
	Copper and copper alloys (bronze/brass)	machining steel, PB > 1%		110	27						
		CuZn, CuSnZn		90	28						
CuSn, Pb-free copper, electrolytic copper		100	29								
S	Heat-resistant alloys	Fe-based alloys	annealed	200	30						
			hardened	280	31						
		Ni or Co base	annealed	250	32						
			hardened	350	33						
	cast	320	34								
Titanium alloys	pure titanium		R_m 400	35							
α and β alloys	hardened		R_m 1050	36							
H	Hardened steel		hardened and tempered	55 HRC	37						
			hardened and tempered	60 HRC	38						
	Hard cast iron		cast	400	39						
	Hardened cast iron		hardened and tempered	55 HRC	40						
X	Non-metallic materials	Thermoplasts			41						
		Thermosetting plastics			42						
		Plastic, glass-fibre reinforced GFRP			43						
		Plastic, carbon fibre reinforced CFRP			44						
		Graphite			45						
		Wood			46						

Note: The given cutting values are guide values, which were determined under ideal conditions.
 The values have to be adapted in individual cases.
 Feed rate recommendations on page B240.
 For examples of material for cutting tool groups view page D22.

Starting values for cutting speed v_c [m/min]				
	HC (PVD)			
	YBG302			
	a_e / D			
	1/1 3/4	1/5	1/20	
	200	230	300	
	170	200	260	
	160	185	245	
	140	165	215	
	130	150	195	
	170	200	260	
	140	165	215	
	130	150	195	
	110	130	170	
	100	115	150	
	70	85	115	
	100	115	150	
	85	100	130	
	110	125	160	
	85	100	130	
	220	255	335	
	130	150	195	
	150	175	230	
	100	115	150	
	180	210	275	
	120	140	185	

HC Coated carbide
 HT Uncoated carbide, main component (TiC) o. (TiN), cermet
 HC₁ Coated cermet
 HW Uncoated carbide, main component (WC)

A
 Turning
B
 Milling
C
 Drilling
D
 Technical Information
E
 Index



Recommend feed rate

Indexable milling – group 4 (BMR01/02/03/04, TMP01, CMZ01, CMA01, CMD01)

Material group		Feed rate per cutting edge [mm]								
		BMR01	BMR01	BMR01	BMR01	BMR02	BMR02	BMR02	BMR03	BMR03
		ZD*08 / SP*06	ZD*11 / SP*06	ZD*13 / SP*09	ZP*22 / SP*12	ROHX12	ROHX16	ROHX20	-	-
		Tool diameter [mm]								
		20	25	32	40-63	12	16	20	16	20
P	Unalloyed steel	0,14	0,21	0,26	0,32	0,10	0,13	0,14	0,13	0,14
	Low-alloyed steel	0,10	0,15	0,18	0,22	0,07	0,09	0,10	0,09	0,10
	High-alloyed steel and high-alloyed tool steel	0,09	0,14	0,17	0,21	0,07	0,08	0,09	0,08	0,09
M	Stainless steel	0,08	0,12	0,14	0,18	0,06	0,07	0,08	0,07	0,08
K	Grey cast iron	0,18	0,27	0,34	0,42	0,13	0,17	0,18	0,17	0,18
	Cast iron with spheroidal graphite	0,13	0,20	0,25	0,30	0,10	0,12	0,13	0,12	0,13
	Malleable cast iron	0,14	0,21	0,26	0,32	0,10	0,13	0,14	0,13	0,14
N	Aluminium wrought alloys									
	Aluminium-Gusslegierungen									
	Copper and copper alloys(bronze/brass)									
S	Heat-resistant alloys									
	Titanium alloys									
H	Hardened steel									
	Hard cast iron									
	Hardened cast iron									
X	Non-metallic materials									

Hinweis: Bei den vorgegebenen Schnittwerten handelt es sich um Richtwerte, welche unter Idealbedingungen ermittelt wurden.
In individuellen Anwendungsfällen sind die Werte anzupassen.

Indexable milling – group 5 (SMP01/03/05)

Material group		Feed rate per cutting edge [mm]								
		SMP01	SMP01	SMP01	SMP01	SMP01	SMP03	SMP03	SMP03	SMP05
		XSEQ1202	XSEQ1203	XSEQ12T3	XSEQ1204	XSEQ12T4	MPHT06	MPHT08	MPHT12	QC16
		Tool diameter [mm]								
		63-100	63-100	63-160	63-160	63-160	80-125	125-200	120-200	25-39
P	Unalloyed steel	0,12	0,12	0,13	0,13	0,14	0,14	0,15	0,16	0,08
	Low-alloyed steel	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,08
	High-alloyed steel and high-alloyed tool steel	0,10	0,10	0,11	0,11	0,12	0,12	0,13	0,14	0,07
M	Stainless steel	0,10	0,10	0,11	0,11	0,12	0,12	0,13	0,14	0,07
K	Grey cast iron	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,08
	Cast iron with spheroidal graphite	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,07
	Malleable cast iron	0,11	0,11	0,12	0,12	0,13	0,13	0,14	0,15	0,07
N	Aluminium wrought alloys									
	Aluminium-Gusslegierungen									
	Copper and copper alloys(bronze/brass)									
S	Heat-resistant alloys									
	Titanium alloys									
H	Hardened steel									
	Hard cast iron									
	Hardened cast iron									
X	Non-metallic materials									

Hinweis: Bei den vorgegebenen Schnittwerten handelt es sich um Richtwerte, welche unter Idealbedingungen ermittelt wurden.
In individuellen Anwendungsfällen sind die Werte anzupassen.

A

Turning

B

Milling

C

Drilling

D















Technical
Information

E

Index

		Feed rate per cutting edge [mm]											
		BMR03	BMR03	BMR03	BMR04	BMR04	BMR04	BMR04	BMR04	CMZ01	CMA01	CMD01	
		-	-	-	ZOHX12	ZOHX16	ZOHX20	ZOHX25	ZOHX30	SPMT12	SPMT12	SPMT12	
		Tool diameter [mm]											
		25	30-32	40-50	12	16	20	25	30	12-32	12-32	12-36	
	0,21	0,26	0,30	0,10	0,13	0,14	0,16	0,17	0,23	0,23	0,23		
	0,15	0,18	0,21	0,07	0,09	0,10	0,11	0,12	0,16	0,16	0,16		
	0,14	0,17	0,20	0,07	0,08	0,09	0,10	0,11	0,15	0,15	0,15		
	0,12	0,14	0,17	0,06	0,07	0,08	0,09	0,09	0,13	0,13	0,13		
	0,27	0,34	0,39	0,13	0,17	0,18	0,21	0,22	0,30	0,30	0,30		
	0,20	0,25	0,29	0,10	0,12	0,13	0,15	0,16	0,22	0,22	0,22		
	0,21	0,26	0,30	0,10	0,13	0,14	0,16	0,17	0,23	0,23	0,23		

		Feed rate per cutting edge [mm]											
		SMP05											
		QC22											
		Tool diameter [mm]											
		44											
	0,08												
	0,08												
	0,07												
	0,07												
	0,08												
	0,07												
	0,07												

	Series	Milling body	Inserts	Kr	Application						Features	Page
					P	M	K	N	S	H		
Chamfer milling	CMZ01		 SPMT1204	30°	✓	✓	✓				<ul style="list-style-type: none"> • Diameter range Ø12 – 32 mm • For steel, stainless steel and cast iron • Chamfer milling cutter 30° 	B174 -177
	CMA01		 SPMT1204	45°	✓	✓	✓				<ul style="list-style-type: none"> • Diameter range Ø12 – 32 mm • For steel, stainless steel and cast iron • Chamfer milling cutter 45° • Weldon shank 	B178 -181
	CMD01		 SPMT1204	60°	✓	✓	✓				<ul style="list-style-type: none"> • Diameter range Ø12 – 32 mm • For steel, stainless steel and cast iron • Chamfer milling cutter 60° • Weldon shank 	B182
Indexable heads – QCH series	QCH-XPHT		 XPHT16 XPHT20 XPHT25 XPHT30 XPHT32		✓	✓	✓				<ul style="list-style-type: none"> • Diameter range Ø16 – 32 mm • For steel and cast iron • Very suitable for roughing in mould and die industry 	B188
	QCH-SDMT		 SDMT06T2 SDMT09T3 SDMT1204 SDMT1505	15°	✓	✓	✓				<ul style="list-style-type: none"> • Diameter range Ø20 – 40 mm • For steel, stainless steel and cast iron • Inserts with four cutting edges • Ramping possible • Double clamping system for inserts 	B190
	QCH-WPGT		 WPGT0503 WPGT0604 WPGT0806 WPGT0907	11° - 22°	✓	✓	✓				<ul style="list-style-type: none"> • Diameter range Ø16 – 42 mm • For steel, stainless steel and cast iron • Inserts with three cutting edges • Ramping possible • Double clamping system for inserts 	B192
	QCH-APKT		 APKT11T3 APKT1604	90°	✓	✓	✓	✓	✓		<ul style="list-style-type: none"> • Diameter range Ø16 – 40 mm • For steel, stainless steel, cast iron, non-ferrous metals and heat-resistant alloys • For square shoulder milling, slot milling and ramping • Milling cutter with positive, soft cutting geometry • Inserts with two cutting edges 	B194

✓ Very suitable ✓ Suitable

A

Turning

B

Milling

C

Drilling

D

Technical Information









E

Index

Chip breakers overview

	Finishing	Medium machining	Roughing
A Turning	DF	DM	DR
	APF	APM	-
	PF	PM	PR
	GF	GM	GR
	-	-	ZR
	MO-2	MO-1	MO-3
B Milling	EF	EM	-
	APF	APM	-
	DF	DM	-
	PF	PM	PR
	GF	GM	GR
	E	E	-
C Drilling	-	-	ZR
	CF	CM	CR
	DF	DM	DR
	EDFR	DER	DER
	PF	PM	PR
	GF	GM	GR
D Technical Information	-	-	ZR
	MO-2	MO-1	MO-3
	EF	EM	-
E Index	NM	NM	-
	LH	LH	LH
	ALH	ALH	ALH

Coated cemented carbide CVD

Grade	ISO	Micro structure	Grade description
YBC301	P20–P35		CVD coated P20–P35 carbide grade for medium operation to roughing of steel at lower cutting speed.
YBC302	P20–P35		CVD coated P20–P35 carbide grade for medium operation to roughing of steel at higher cutting speed. Optimal performance of wear resistance and toughness for a wide application field.
YBC401	P30–P50 M30–M40		CVD coated P30–P50/M30–M40 carbide grade for roughing operation of steel at lower cutting speed and unstable condition.
YBM251	P20–P30 M15–M35		CVD coated P20–P30/M15–M35 carbide grade for medium to roughing operation in stainless steel and steel with wide application field. Good wear resistance and capability against plastic deformation at normal cutting speed.
YBM253	M15–M35		CVD coated M15–M35 carbide grade for medium to roughing operation in stainless steel with wide application field. High wear resistance and capability against plastic deformation at higher cutting speed.
YBM351	P25–P40 M25–M40		CVD coated P25–P40/M25–M40 carbide grade for roughing operation in stainless steel and steel. Good wear resistance and edge stability at normal cutting speed.
YBD152	K10–K25		CVD coated K10–K25 carbide substrate. Optimized for medium to roughing operation of cast iron. Good wear resistance and toughness at higher cutting speed.
YBD252	K20–K35		CVD coated K20–K35 carbide substrate. Optimized for medium to roughing operation of cast iron and Steel. Good wear resistance and toughness at higher cutting speed.

A

Turning

B

Milling






C

Drilling

DTechnical
Information**E**

Index

Coated cemented carbide PVD

Grade	ISO	Micro structure	Grade description
YBG102	S05–S15		PVD coated S05–S15 carbide substrate for finishing to medium application of super alloy material, stainless steel and aluminum. Good wear resistance in a wide application field.
YBG202	P10–P30 M10–M25		PVD coated P10–P30/M10–M25 carbide substrate for finishing to medium application of stainless steel and steel (milling). Good wear resistance in a wide application field.
YB9320	P10–P30 M20–M40		PVD multilayer coated P10–P30/M20–M40 carbide substrate for finishing to medium application of stainless steel, super alloy and steel (grooving/milling). Optimized coating stability for higher wear resistance and thermal stability in a wide application field.
YBG205	P10–P30 M20–M40 S15–S25		PVD multilayer coated P10–P30/M20–M40/S15–S25 carbide substrate for finishing to medium application of stainless steel, super alloy and steel (milling). Good wear resistance and thermal stability in a wide application field.
YBG302	P15–P30 M25–M40		PVD coated P15–P30/M25–M40 carbide substrate for medium roughing application of stainless steel and steel (milling). Good wear resistance and toughness.
YBG152	K20–K35	–	PVD coated K20–K35 carbide substrate for medium roughing application of cast iron. Good wear resistance and toughness.
YBG252	P10–P20 M10–M20 K10–K20	–	PVD coated P10–P20/M10–M20/K10–K20 carbide grade for finishing to medium operation of steel, stainless steel and cast iron. Good wear resistance and toughness for a wide application field.

A

Turning

B

Milling

C

Drilling



D

Technical Information




E

Index

Cermet

Grade	ISO	Micro structure	Grade description
YNG151	P05–P15		Uncoated P05–P15 cermet grade for fine finishing operation of steel and stainless steel. Good resistance against plastic deformation for good surface finishing.
YNG151C	P05–P15		PVD coated P05–P15 cermet grade for fine finishing operation of steel and stainless steel. Good wear resistance and capability against plastic deformation for good surface roughness.

Uncoated cemented carbide

Grade	ISO	Micro structure	Grade description
YC30S	P25–P40 M25–M40		Uncoated P25–P40/M25–M40 carbide substrate for roughing operation of steel and stainless steel.
YD101	K05–K20 N05–N20		Uncoated K05–K20/N05–N20 carbide substrate for fine to medium application in aluminum and other material.
YD201	K10–K30 N10–N30		Uncoated K10–K30/N10–N30 carbide substrate for medium application in aluminum and other material.

A

Turning

B

Milling

C

Drilling

DTechnical
Information**E**

Index

Application fields of grades – Indexable milling

	ISO	HC ¹ (CVD)	HC ¹ (PVD)	HT	HC ²	HW	PCBN/PCD
P	P01		YBG102		YNG151C		
	P10		YBG202	YNG151			
	P20	YBC301	YBG205				
	P30	YBC401	YBG252			YC305	
	P40	YBM351	YBG302				
		YBM253	YB9320				
M	M01		YBG102		YNG151C		
	M10	YBM251	YBG202	YNG151			
	M20	YBM253	YBG205				
	M30	YBM351	YBG252			YC305	
	M40	YBC401	YBG302				
			YB9320				
K	K01		YBG102				
	K10	YBD152	YBG152				
	K20	YBD252	YBG202			YD201	
	K30		YBG252				
	K40						
N	N01					YD051	
	N10		YBG101			YD101	
	N20		YBG202			YD201	
	N30						
S	S01		YBG102				
	S10		YBG202				
	S20		YBG205				
	S30						
H	H01		YBG102				
	H10						
	H20						
	H30						

P	Steel
M	Stainless steel
K	Cast iron

N	Non-ferrous metals
S	Heat-resistant alloys
H	Hardened materials

HC¹ Coated carbide
 HT Uncoated cermet
 HC² Coated cermet
 HW Uncoated carbide